

	Technical Data Sheet
Issue June 2022	for professional use only

KRLO - 100/70WS Alkyd resin

Product description

KRLO - 100 is a long oil air drying alkyd resin used for wide assortment of paints and clearcoats. KRLO - 100 is especially designed for use in conventional air-drying primers and finishes. It is delivered as 70% in White Spirit.

Use:

- Exterior and interior glossy enamels
- Primers
- Wood clearcoats
- Floor sealers

Features:

- High gloss
- Very good yellowing resistance
- Very good adhesion

Chemical properties:

Type of polyol	Glycol-Pentaerythritol
Oil type	Soybean oil
Type of solvent:	White Spirit
Oil content	59%
PA	28%

Physical properties:

Solid content	70±2 %
Viscosity	Z6-Z7
Acid value: max	10 mg KOH/g
Color (Gardner)	max 5

Storage:

Store in original container at normal temperature and dry conditions. Temperature should not



exceed 40°C. Store in well ventilated area.

Shelf life:

24 months, stored under the given above storage conditions.

General note:

The product can be delivered with different viscosity and acid value, as per customer requirements.

Health and Safety

- 1. For full Health and Safety information please refer to the Material Safety Data Sheet.
- 2. Observe the precautionary notices displayed on the container.
- 3. Good ventilation must be provided in the working environment.