



KAPCI
COATINGS

Technical Data Sheet

Issue Date June 2022

For professional use only

Kapci 2620 1K Polyurethane glossy clearcoat for Interior

Product properties

Kapci 2620 is a 1K polyurethane glossy clearcoat used for the protection of wooden substrates in interior. It is recommended for finishing indoor woodworks (doors, partitions, wall-units, ceiling, etc), room furniture including built-in closets, tables, chairs, cupboards, etc. It provides easy application, very good leveling and smoothness and very good resistance against water and common household chemicals.

Gloss: min 88 GU (angle 60°)

Theoretical coverage: 5-6 m²/l per a coat

Products for application

Kapci 2620 1K PU Glossy Clearcoat

Kapci 555 Thinner or White Spirit thinner

Substrate and surface preparation

Kapci 2620 is suitable for application over all kind of wooden surfaces previously painted with Kapci NC sealer. If the surface needs to be colored, apply Kapci 2800 Wood Stain prior to applying Kapci NC sealer. Sand the sealer with P320 grit paper followed with P400 and finish with P500.

Application



Mixing ration and application

Add 35-40% thinner for spraying.

Apply in 2 single coats.



Add 15-20% thinner for brush.

Apply in 2 single coats.



Dry to touch: 60-90 min/25°C

Dry to handle: 6-8 h/25°C

Dry to recoat: 6-8 h/25°C

Other tips

1. The wooden surface coated with Kapci 2620 might be cleaned by using a damp cloth after 3 days of drying of the final coat.
2. Practical coverage depends on several factors including shape, roughness and porosity of the object to be painted, spraying equipment used, application methods, application conditions, film thickness, etc.

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.



KAPCI
COATINGS

Shelf life

3 years from production date stored in original packaging at normal conditions.

Health and Safety

1. For full Health and Safety information please refer to the Material Safety Data Sheet.
2. Observe the precautionary notices displayed on the container.
3. Good ventilation must be provided in the working environment.

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.