



KAPCI
COATINGS

Technical Data Sheet

Issue date June 2022

For professional use only

Kapci 2820 wood stain

Product properties

Kapci 2820 is concentrated solvent-based wood stain. It is specially designed for coloring of wooden surfaces before applying nitrocellulose, synthetic, polyester and polyurethane transparent finishes when natural look of wood is desired. It penetrates bare wood, provides fast drying and good light fastness and can be used for coloring of wooden surfaces indoor. The product is offered in a pallet of shades according to Kapci Wood Stains color chart.

Theoretical coverage: 8-10 m²/l per a coat

Products for application

Kapci 2820 Wood Stain

Kapci 526 NC thinner/ or Turpentine

Substrates and surface preparation

Sand the surface of solid wood with P80-P120 grit paper. For MDF, plywood or veneer, use finer grit paper P150 or P180. Blow off dust and degrease the surface.

Application



Mixing ratio: Mix 1 part of Kapci 2820 wood stain with 1 Parts of Kapci 526 NC or Turpentine get the same color in the swatch



Apply several coats by brush or by lint-free cotton to get the desired shade.



Dry to overcoat: 15-20 min/25°C

Other tips

1. Kapci 2820 should be shaken well before use.
2. Practical coverage depends on several factors including shape, roughness and porosity of the object to be painted, spraying equipment used, application methods, application conditions, film thickness, etc.

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.



KAPCI
COATINGS

Shelf life

3 years from production date, stored in original packaging at normal conditions.

Health and Safety

1. For full Health and Safety information refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Good ventilation must be provided in the working environment.