



Technical Data Sheet

Issue date June 2022

for professional use only

Kapci Polyurethane Thinners and Reducers

Product description

Kapci PU Thinners are especially designed to suite the application viscosity and the drying time of Kapci Wood Finish products when used with Kapci Hardeners. Kapci Thinners optimize all painting conditions and assist in delivering highly reliable application processes.

Products

Product	Description		
Kapci 2450	Normal Thinner	Suitable for Polyurethane products as Pu clear coats, Pu sealers and Ws100	See Technical Data Sheet of Base Products
Kapci 2460	Slow Thinner	Suitable for Polyurethane products as Pu clear coats, Pu sealers and Ws100	See Technical Data Sheet of Base Products
WS160	Normal Thinner	Suitable for Polyurethane products as Pu clear coats, Pu sealers and Ws100	See Technical Data Sheet of Base Products

Choice of thinners

The recommendations in the table below are for guidance only. Please refer to TDSs of the respective 2K products for more detailed information about the selection of the Thinners.

Suitable for	Normal 2450andWs160	Slow 2460
Complete car or large objects	Suitable	Suitable
Partial repair	Suitable	Suitable
15°C - 20°C	Suitable	Unsuitable
20°C- 25°C	Suitable	Not particularly suitable
Above 30°C	Suitable	Suitable
Above 35°C	Not particularly suitable	Suitable

Health and Safety

1. For full Health and Safety information please refer to Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.