

Page 1/8

## Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 27.03.2023

Revision: 27.03.2023

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Kapci 2155

- Article number: 2155
- *Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.*
- Application of the substance / the mixture .

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Kapci Coatings Industrial Zone El - Raswa Port Said EGYPT mohamed.khalil@kapci.com

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +20 66 3770000

### **2** Hazards identification

· Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

· Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. • Hazard pictograms



Signal word Danger
Hazard statements
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
Precautionary statements
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.

(Contd. on page 2)

GB

Printing date 27.03.2023

Revision: 27.03.2023

#### Trade name: Kapci 2155

	(Contd. of page 1)
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	P IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	<i>F IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</i>
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Other hazards	
· Results of PBT and	d vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

#### **3** Composition/information on ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	Xylene	25-50%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
01-2119486136-34-		
XXXX		
	ethyl acetate	10-25%
	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119475103-46	the working of the listed har and physical poly to gootion 16	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

### 4 First aid measures

#### · Description of first aid measures

#### • General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.

• Information for doctor:

· Most important symptoms and effects, both acute and delayed Breathing difficulty

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 2155

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

#### **6** Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions:
   Do not allow product to reach sewage system or any water course.
   Inform respective authorities in case of seepage into water course or sewage system.
   Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
   Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- *Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.*
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see section 7.

· Control parameters

Ingredients with limit values that require monitoring at the workplace:	
1330-20-7 Xylene	
WEL Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm	
Sk; BMGV	
141-78-6 ethyl acetate	
WEL Short-term value: 1468 mg/m³, 400 ppm	
Long-term value: 734 mg/m³, 200 ppm	
	(Contd. on page 4

(Contd. of page 2)

Printing date 27.03.2023

Revision: 27.03.2023

#### Trade name: Kapci 2155

Inoredi	ents with biological limit val	(Contd. of page 2
-	0-7 Xylene	ues.
	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric	acid
Persona Genera Keep av Immedi Wash h Avoid c Avoid c Respira In case use self	re controls al protective equipment: l protective and hygienic med way from foodstuffs, beverage ately remove all soiled and co ands before breaks and at the ontact with the skin. ontact with the eyes and skin. tory protection:	<b>asures:</b> es and feed. ontaminated clothing e end of work. ution use respiratory filter device. In case of intensive or longer exposu.
Due to the cher Selection degraded Materia The selection and van resistant applica Penetra The exact observe	ve material has to be imperm missing tests no recommenda mical mixture. on of the glove material of ation al of gloves ection of the suitable gloves a ries from manufacturer to m ace of the glove material can tion. ution time of glove material act break through time has to	teable and resistant to the product/ the substance/ the preparation. In the glove material can be given for the product/ the preparation of the penetration times, rates of diffusion and the loes not only depend on the material, but also on further marks of quali anufacturer. As the product is a preparation of several substances, the not be calculated in advance and has therefore to be checked prior to the be found out by the manufacturer of the protective gloves and has to be
	Tightly sealed goggles	
<b>Physic</b>	cal and chemical proper	ties
Inform	ation on basic physical and c	chemical properties
	l Information	
Appear Form		Fluid
Colou	ır:	According to product specification
Odour:		Characteristic
undour	threshold:	Not determined.

· pH-value:

• Change in condition Melting point/freezing point:

Undetermined.

Not determined.

(Contd. on page 5)

GB -

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 2155

	(Contd. of page 4
Initial boiling point and boiling range	:: 77 °C
· Flash point:	-1 °C
· Flammability (solid, gas):	Highly flammable.
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density:	Not determined.
Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	44.3 %
VOC (EC)	44.31 %
Solids content:	55.7 %
• Other information	No further relevant information available.

### **10 Stability and reactivity**

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### **11 Toxicological information**

· Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 Xylene

*Oral LD50 4,300 mg/kg (rat)* 

Dermal LD50 2,000 mg/kg (rabbit)

• Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

(Contd. on page 6)

<sup>-</sup> GB

Printing date 27.03.2023

Revision: 27.03.2023

#### Trade name: Kapci 2155

- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- $\cdot$  Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Reproductive toxicity Based on available data, the classification criteria are not met.}$
- STOT-single exposure Based on available data, the classification criteria are not met.
- $\cdot \textbf{STOT-repeated exposure} Based on available data, the classification criteria are not met.$
- Aspiration hazard Based on available data, the classification criteria are not met.

#### **12 Ecological information**

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· ADR, IMDG, IATA	UN1263	
$\cdot$ UN proper shipping name		
$\cdot ADR$	1263 PAINT	
· IMDG, IATA	PAINT	
· Transport hazard class(es)		
· ADR, IMDG, IATA		
· Class	3 Flammable liquids.	

(Contd. of page 5)

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 2155

	(Contd. of pa
Label	3
Packing group	
ADR, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	В
Transport in bulk according to Annex II of Mar	pol
and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: E2
-	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN ''Model Regulation'':	UN 1263 PAINT, 3, II

### **15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.

· Department issuing SDS: Quality Assurance & Environment Departement

· Contact: Chemist / Mohamed Khalil

(Contd. on page 8)

GB

Printing date 27.03.2023

Revision: 27.03.2023

# Trade name: Kapci 2155

(Contd. of page 7)	
· Abbreviations and acronyms:	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the	
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
GB	-