

Page 1/8

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 27.03.2023

Revision: 27.03.2023

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

• Trade name: Kapci 2170

- Article number: 2170
- *Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.*
- · Application of the substance / the mixture .

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Kapci Coatings Industrial Zone El - Raswa Port Said EGYPT mohamed.khalil@kapci.com

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +20 66 3770000

2 Hazards identification

· Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. • Hazard pictograms



· Signal word Warning

• *Hazard-determining components of labelling: N-Butyl acetate*

- · Hazard statements
- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- · Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 2170

| | (Contd. of page 1) |
|------------------|---|
| P102 | Keep out of reach of children. |
| P103 | Read label before use. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P241 | Use explosion-proof [electrical/ventilating/lighting] equipment. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P303+P361+P35 | 53 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Other hazards | |
| Results of PBT a | nd vPvB assessment |

· **PBT:** Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

| CAS: 123-86-4 | N-Butyl acetate | 10-25% |
|---|--|---------|
| EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-0002 | Flam. Liq. 3, H226; STOT SE 3, H336 | |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32 01-2119486136-34-XXXX | Xylene Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | 10-25% |
| CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-0000 01-2119475791-29-XXXX | | 2.5-10% |

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Breathing difficulty
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

GB

Printing date 27.03.2023

Revision: 27.03.2023

(Contd. of page 2)

Trade name: Kapci 2170

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- $\cdot \textit{Environmental precautions: } Do not allow to enter sewers/ surface or ground water.$
- \cdot Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
 Information about fire - and explosion protection:
- *Keep ignition sources away Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · Control parameters
- \cdot Ingredients with limit values that require monitoring at the workplace:

123-86-4 N-Butyl acetate

- WEL Short-term value: 966 mg/m³, 200 ppm
 - Long-term value: 724 mg/m³, 150 ppm

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

(Contd. on page 4)

GB

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 2170

| 100.45 | (Contd. of page 3) |
|--|--|
| | -6 Methoxypropylacetate |
| L | 'hort-term value: 548 mg/m³, 100 ppm .ong-term value: 274 mg/m³, 50 ppm 'k |
| · Ingredi | ients with biological limit values: |
| 1330-2 | 0-7 Xylene |
| BMGV | 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid |
| Persona Genera Keep av Immedi Wash h Avoid c Avoid c Respira In case use self | are controls al protective equipment: al protective and hygienic measures: way from foodstuffs, beverages and feed. iately remove all soiled and contaminated clothing cands before breaks and at the end of work. contact with the skin. contact with the eyes and skin. tory protection: of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure f-contained respiratory protective device. tor of hands: |
| Due to the che Selecti degrad | |
| The self and var resistar applica • Penetra | ation time of glove material act break through time has to be found out by the manufacturer of the protective gloves and has to be |
| · Eye pro | |
| 9 Physic | cal and chemical properties |
| | ation on basic physical and chemical properties Il Information |

- · Appearance:
- Form:FluidColour:According to product specificationOdour:Characteristic

(Contd. on page 5)

⁻ GB

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 2170

| Odour threshold: | (Contd. of page - |
|--|---|
| | |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/freezing point: Initial boiling point and boiling range | Undetermined. |
| Flash point: | 27 °C |
| Flammability (solid, gas): | Flammable. |
| • • • • • • | |
| Auto-ignition temperature: | 333 °C |
| Decomposition temperature: | Not determined. |
| Ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosive air vapour mixtures are possible. |
| Explosion limits: | |
| Lower: | 1.1 Vol % |
| Upper: | 7.5 Vol % |
| Vapour pressure at 20 °C: | 10.7 hPa |
| Density: | Not determined. |
| Relative density | Not determined. |
| Vapour density | Not determined. Not determined. |
| Evaporation rate | Noi delerminea. |
| Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| Partition coefficient: n-octanol/water: | Not determined. |
| Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| Solvent content: | |
| Organic solvents: | 57.0% |
| VOC (EC) | 57.00 % |
| Solids content: | 43.0 % |
| Other information | No further relevant information available. |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

GB

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 2170

| LD/LC50 | values relevant for class | (Contd. of p |
|--|--|---|
| 1330-20-7 | • | |
| | D50 4,300 mg/kg (rat) | |
| Dermal L | D50 2,000 mg/kg (rabb | pit) |
| | rritant effect: | |
| | osion/irritation in irritation. | |
| Respirator Additional CMR effec Germ cell | ry or skin sensitisation E l toxicological informati cts (carcinogenity, muta mutagenicity Based on | agenicity and toxicity for reproduction) available data, the classification criteria are not met. |
| Reproduct | | ole data, the classification criteria are not met. vailable data, the classification criteria are not met. |
| May cause | e drowsiness or dizziness | |
| | | on available data, the classification criteria are not met. lable data, the classification criteria are not met. |
| | | |
| | | |
| Ecologic | cal information | |
| Toxicity | | |
| | | ant information available. further relevant information available. |
| | r in environmental system | |
| | | ther relevant information available. |
| | n soil No further relevan | |
| | l ecological information | n: |
| General n | | |
| | | gulation) (Self-assessment): hazardous for water |
| | | ound water, water course or sewage system. small quantities leak into the ground. |
| | F PBT and vPvB assessm | |
| | applicable. | 10111 |
| | t applicable. | |
| | | relevant information available. |
| | | |
| Disposal | l considerations | |
| | atment methods | |
| Recomme. Must not k | | h household garbage. Do not allow product to reach sewage system. |
| | | n nousenoia garbage. Do noi anow product to reach sewage system. |
| | d packaging: ndation: Disposal must | be made according to official regulations. |
| | nution. Disposai masi | be made according to official regulations. |
| Transpo | ort information | |
| | | |
| UN-Numb | | UN1263 |
| | | 0111205 |
| ADR, IMI | * * * | |
| UN prope | r shipping name | 1263 DAINT |
| | | 1263 PAINT PAINT |

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 2170

| | (Contd. of page |
|---|--|
| Transport hazard class(es) | |
| ADR, IMDG, IATA | |
| | |
| Class | 3 Flammable liquids. |
| Label | 3 |
| Packing group ADR, IMDG, IATA | 111 |
| Environmental hazards: Marine pollutant: | No |
| Special precautions for user | Warning: Flammable liquids. |
| Hazard identification number (Kemler code): | 30 |
| EMS Number: | <i>F-E</i> , <u><i>S-E</i></u> |
| Stowage Category | A |
| Transport in bulk according to Annex II of Marg and the IBC Code | ool Not applicable. |
| Transport/Additional information: | |
| ADR | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| m | Maximum net quantity per outer packaging: 1000 ml |
| Transport category | 3 D/F |
| Tunnel restriction code | D/E |
| IMDG | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: El |
| | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| | |
| UN "Model Regulation": | UN 1263 PAINT, 3, III |

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour. H312 Harmful in contact with skin.

(Contd. on page 8)

GB

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 2170

| | (Contd. of page 7) |
|---|------------------------|
| H315 Causes skin irritation. | |
| H332 Harmful if inhaled. | |
| H336 May cause drowsiness or dizziness. | |
| · Department issuing SDS: Quality Assurance & Environment Departement | |
| Contact: Chemist / Mohamed Khalil | |
| • Abbreviations and acronyms: | |
| ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agree | ement Concerning the |
| International Carriage of Dangerous Goods by Road) | sincent concerning inc |
| IMDG: International Maritime Code for Dangerous Goods | |
| IATA: International Air Transport Association | |
| GHS: Globally Harmonised System of Classification and Labelling of Chemicals | |
| EINECS: European Inventory of Existing Commercial Chemical Substances | |
| ELINCS: European List of Notified Chemical Substances | |
| CAS: Chemical Abstracts Service (division of the American Chemical Society) | |
| VOC: Volatile Organic Compounds (USA, EU) | |
| LC50: Lethal concentration, 50 percent | |
| LD50: Lethal dose, 50 percent | |
| PBT: Persistent, Bioaccumulative and Toxic | |
| vPvB: very Persistent and very Bioaccumulative | |
| Flam. Liq. 3: Flammable liquids – Category 3 | |
| Acute Tox. 4: Acute toxicity – Category 4 | |
| Skin Irrit. 2: Skin corrosion/irritation – Category 2 | |
| STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 | |
| | GB |