

Page 1/8

# Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 25.03.2023

Revision: 25.03.2023

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Kapci 352

- Article number: 352
- *Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.*
- Application of the substance / the mixture .

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Kapci Coatings Industrial Zone El - Raswa Port Said EGYPT mohamed.khalil@kapci.com

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +20 66 3770000

### **2** Hazards identification

· Classification of the substance or mixture

- · Classification according to Regulation (EC) No 1272/2008
- Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

*Repr.* 2 *H361d Suspected of damaging the unborn child.* 

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.

· Label elements

· Labelling according to Regulation (EC) No 1272/2008

*The product is classified and labelled according to the GB CLP regulation.* • *Hazard pictograms* 



· Signal word Danger

- *Hazard-determining components of labelling: Styrene*
- · Hazard statements
- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.

(Contd. on page 2)

Printing date 25.03.2023

Revision: 25.03.2023

#### Trade name: Kapci 352

	(Contd. of page 1)
H361d Suspected of	f damaging the unborn child.
H372 Causes dam	age to the hearing organs through prolonged or repeated exposure.
· Precautionary state	ements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P303+P361+P353	<i>IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].</i>
P305+P351+P338	<i>IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</i>
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
• Other hazards	

- Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.

#### **3** Composition/information on ingredients

#### · Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 100-42-5	Styrene	2.5-10%		
EINECS: 202-851-5	Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Acute Tox.			
Reg.nr.: 01-2119457861-32	4, H332; Skin Irrit. 2, Ĥ315; Eye Irrit. 2, H319			
01-2119457861-32-				
XXXX				
· Additional information: For	the wording of the listed hazard phrases refer to section 16.			

#### 4 First aid measures

#### · Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:

· Most important symptoms and effects, both acute and delayed Breathing difficulty

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **5** Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.

 $(Contd. \ on \ page \ 3)$ 

GB

Printing date 25.03.2023

Revision: 25.03.2023

(Contd. of page 2)

Trade name: Kapci 352

· Advice for firefighters

· Protective equipment: No special measures required.

#### **6** Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
   Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### 7 Handling and storage

· Handling:

- *Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.*
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- $\cdot \textit{Further information about storage conditions: Keep container tightly sealed.}$
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see section 7.

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

100-42-5 Styrene

WEL Short-term value: 1080 mg/m<sup>3</sup>, 250 ppm Long-term value: 430 mg/m<sup>3</sup>, 100 ppm

#### · Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

• **Respiratory protection:** 

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 4)

GB -

Printing date 25.03.2023

Revision: 25.03.2023

(Contd. of page 3)

#### Trade name: Kapci 352

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and chem General Information	cical properties
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range.	: 145 °C
Flash point:	31 °C
Flammability (solid, gas):	Flammable.
Auto-ignition temperature:	480 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air, vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
Vapour pressure at 20 °C:	6 hPa
Density:	Not determined.
Relative density	Not determined.

- GB

Printing date 25.03.2023

Revision: 25.03.2023

Trade name: Kapci 352

	(Contd. of	page 4)
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	10.0 %	
VÕC (EC)	10.00 %	
Solids content:	90.0 %	
· Other information	No further relevant information available.	

# 10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# **11 Toxicological information**

· Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

### 100-42-5 Styrene

 Oral
 LD50
 5,000 mg/kg (rat)

 Inhalative
 LC50/4 h
 24 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- $\cdot$  Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity
- Suspected of damaging the unborn child.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 25.03.2023

Revision: 25.03.2023

(Contd. of page 5)

#### Trade name: Kapci 352

**12 Ecological information** 

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

### **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
ADR, IMDG, IATA	UN1263
UN proper shipping name	
ADR	1263 PAINT RELATED MATERIAL solution
IMDG, IATA	PAINT RELATED MATERIAL solution
Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group	
ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	39
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
Stowage Category	A
Transport in bulk according to Annex II of Mar	
and the IBC Code	Not applicable.

Printing date 25.03.2023

Revision: 25.03.2023

Trade name: Kapci 352

	(Contd. of page 6)
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
$\cdot$ Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
$\cdot$ Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN 1263 PAINT RELATED MATERIAL SOLUTION, 3,
-	III

### **15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

· Department issuing SDS: Quality Assurance & Environment Departement

· Contact: Chemist / Mohamed Khalil

· Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 (Contd. on page 8)

GB

Printing date 25.03.2023

Revision: 25.03.2023

#### Trade name: Kapci 352

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 (Contd. of page 7)

GB