



**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.03.2023

Revision: 25.03.2023

**1 Identification of the substance/mixture and of the company/undertaking**

- **Product identifier**
- **Trade name:** Kapci 465
- **Article number:** 465
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture .**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Kapci Coatings  
Industrial Zone El - Raswa  
Port Said  
EGYPT  
mohamed.khalil@kapci.com
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +20 66 3770000

**2 Hazards identification**

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
Flam. Liq. 2 H225 Highly flammable liquid and vapour.  
Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2 H319 Causes serious eye irritation.  
Repr. 2 H361d Suspected of damaging the unborn child.  
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.  
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**  
toluene
- **Hazard statements**  
H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.

(Contd. on page 2)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 25.03.2023

Revision: 25.03.2023

**Trade name: Kapci 465**

(Contd. of page 1)

*H319 Causes serious eye irritation.**H361d Suspected of damaging the unborn child.**H373 May cause damage to organs through prolonged or repeated exposure.**H304 May be fatal if swallowed and enters airways.***Precautionary statements***P101 If medical advice is needed, have product container or label at hand.**P102 Keep out of reach of children.**P103 Read label before use.**P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.**P321 Specific treatment (see on this label).**P331 Do NOT induce vomiting.**P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].**P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P362+P364 Take off contaminated clothing and wash it before reuse.**P405 Store locked up.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.***Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

### 3 Composition/information on ingredients

**Chemical characterisation: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-0036	<i>toluene</i> Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-0002	<i>N-Butyl acetate</i> Flam. Liq. 3, H226; STOT SE 3, H336	2.5-10%
CAS: 111-76-2 EINECS: 203-905-0	<i>2-butoxyethanol</i> Acute Tox. 3, H311; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-10%
CAS: 78-83-1 EINECS: 201-148-0	<i>butanol</i> Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≤2.5%
CAS: 78-93-3 EINECS: 201-159-0	<i>butanone</i> Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	≤2.5%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First aid measures

**Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**After inhalation:** In case of unconsciousness place patient stably in side position for transportation.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 25.03.2023

Revision: 25.03.2023

**Trade name: Kapci 465**

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** Breathing difficulty
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.

(Contd. on page 4)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 25.03.2023

Revision: 25.03.2023

Trade name: Kapci 465

(Contd. of page 3)

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**108-88-3 toluene**

WEL	Short-term value: 384 mg/m <sup>3</sup> , 100 ppm Long-term value: 191 mg/m <sup>3</sup> , 50 ppm Sk
-----	--

**123-86-4 N-Butyl acetate**

WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
-----	---

**111-76-2 2-butoxyethanol**

WEL	Short-term value: 246 mg/m <sup>3</sup> , 50 ppm Long-term value: 123 mg/m <sup>3</sup> , 25 ppm Sk, BMGV
-----	---

**78-83-1 butanol**

WEL	Short-term value: 231 mg/m <sup>3</sup> , 75 ppm Long-term value: 154 mg/m <sup>3</sup> , 50 ppm
-----	---

**78-93-3 butanone**

WEL	Short-term value: 899 mg/m <sup>3</sup> , 300 ppm Long-term value: 600 mg/m <sup>3</sup> , 200 ppm Sk, BMGV
-----	---

· **Ingredients with biological limit values:**

**111-76-2 2-butoxyethanol**

BMGV	240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid
------	---

**78-93-3 butanone**

BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
------	---

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 25.03.2023

Revision: 25.03.2023

**Trade name: Kapci 465**

(Contd. of page 4)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

· <b>Form:</b>	Fluid
· <b>Colour:</b>	According to product specification
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Initial boiling point and boiling range:</b>	110 °C

- **Flash point:** 4 °C

- **Flammability (solid, gas):** Highly flammable.

- **Auto-ignition temperature:** 370 °C

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

· <b>Lower:</b>	1.2 Vol %
· <b>Upper:</b>	7 Vol %

- **Vapour pressure at 20 °C:** 29 hPa

- **Density:** Not determined.

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

- **Partition coefficient: n-octanol/water:** Not determined.

- **Viscosity:**

- **Dynamic:** Not determined.

- **Kinematic:** Not determined.

(Contd. on page 6)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 25.03.2023

Revision: 25.03.2023

Trade name: Kapci 465

(Contd. of page 5)

<b>· Solvent content:</b>	
<b>Organic solvents:</b>	30.7 %
<b>VOC (EC)</b>	30.71 %
<b>· Solids content:</b> 69.3 %	
<b>· Other information</b> No further relevant information available.	

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

<b>111-76-2 2-butoxyethanol</b>		
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**  
Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**  
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 7)

# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 25.03.2023

Revision: 25.03.2023

Trade name: Kapci 465


(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

<b>· UN-Number</b>	UN1263
<b>· ADR, IMDG, IATA</b>	
<b>· UN proper shipping name</b>	1263 PAINT
<b>· ADR</b>	1263 PAINT
<b>· IMDG, IATA</b>	PAINT
<b>· Transport hazard class(es)</b>	
<b>· ADR, IMDG, IATA</b>	
	
<b>· Class</b>	3 Flammable liquids.
<b>· Label</b>	3
<b>· Packing group</b>	II
<b>· ADR, IMDG, IATA</b>	
<b>· Environmental hazards:</b>	Not applicable.
<b>· Special precautions for user</b>	Warning: Flammable liquids.
<b>· Hazard identification number (Kemler code):</b>	33
<b>· EMS Number:</b>	F-E, <u>S-E</u>
<b>· Stowage Category</b>	B
<b>· Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
<b>· Transport/Additional information:</b>	
<b>· ADR</b>	
<b>· Limited quantities (LQ)</b>	5L
<b>· Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<b>· Transport category</b>	2
<b>· Tunnel restriction code</b>	D/E

(Contd. on page 8)



# Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 25.03.2023

Revision: 25.03.2023

**Trade name: Kapci 465**

(Contd. of page 7)

· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, II

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c** FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

### · **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.

### · **Department issuing SDS:** Quality Assurance & Environment Departement

· **Contact:** Chemist / Mohamed Khalil

### · **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Acute Tox. 3: Acute toxicity – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 9)



**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.03.2023

Revision: 25.03.2023

**Trade name: Kapci 465**

(Contd. of page 8)

*Repr. 2: Reproductive toxicity – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1*

GB