

Page 1/8

## Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 27.03.2023 Revision: 27.03.2023

## 1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Kapci 602
- · Article number: 602
- $\cdot \textit{Relevant identified uses of the substance or mixture and uses advised against}$

No further relevant information available.

- · Application of the substance / the mixture .
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kapci Coatings

Industrial Zone El - Raswa

Port Said

**EGYPT** 

mohamed.khalil@kapci.com

- · Further information obtainable from: Product safety department
- · Emergency telephone number: During normal opening times: +20 66 3770000

## 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Lahel elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS0

- · Signal word Danger
- · Hazard-determining components of labelling:

Solvent Naphtha 100

N-Butyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H340 May cause genetic defects.

(Contd. on page 2)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 602

(Contd. of page 1)

H350 May cause cancer.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

*P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.* 

*P331* Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-95-6	Solvent Naphtha 100	25-50%
EINECS: 265-199-0 Reg.nr.: 01-2119486773-24-XXXX 01-2119455851-35-XXXX	Flam. Liq. 3, H226; Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304; Acute Tox. 4, H332	
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-0000 01-2119475791-29-XXXX	Methoxypropylacetate Flam. Liq. 3, H226	10-25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-0002	N-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	10-25%

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Breathing difficulty
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

(Contd. on page 3)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 602

(Contd. of page 2)

· For safety reasons unsuitable extinguishing agents: Water with full jet

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

### 108-65-6 Methoxypropylacetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

#### 123-86-4 N-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 4)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 602

(Contd. of page 3)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 124 °C

· Flash point:  $27 \, ^{\circ}C$ 

· Flammability (solid, gas): Flammable.

· Auto-ignition temperature: 333 °C

· Decomposition temperature: Not determined.

(Contd. on page 5)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 602

	(Contd. of page 4	
· Ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.	
· Explosion limits:		
Lower:	0.7 Vol %	
Upper:	7.5 Vol %	
· Vapour pressure at 20 °C:	10.7 hPa	
Density at 20 °C:	0.8975 g/cm³	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	100.0 %	
VOC (EC)	100.00 %	
Other information	No further relevant information available.	

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:					
64742-95-	64742-95-6 Solvent Naphtha 100				
Oral	LD50	>6,800 mg/kg (rat)			
Dermal	<i>LD50</i>	>3,400 mg/kg (rab)			
Inhalative	LC50/4 h	>10.2 mg/l (rat)			

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity

May cause genetic defects.

(Contd. on page 6)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 602

(Contd. of page 5)

· Carcinogenicity

May cause cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

## 14 Transport information

	<i>111</i>	<i>J_</i> λ	um	hor
•	UI	7 – 1 V	um	nei

· ADR, IMDG, IATA UN1263

· UN proper shipping name

· ADR

1263 PAINT RELATED MATERIAL

· IMDG, IATA PAINT RELATED MATERIAL

- · Transport hazard class(es)
- · ADR, IMDG, IATA



· Class 3 Flammable liquids.

·Label

(Contd. on page 7)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 602

	(Contd. of pa
· Packing group · ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	No
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
Transport in bulk according to Annex II of Marp and the IBC Code	pol Not applicable.
Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml
Transport category Tunnel restriction code	Maximum net quantity per outer packaging: 1000 ml 3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN 1263 PAINT RELATED MATERIAL, 3, III

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- $\cdot \textit{Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000\ t}$
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H340 May cause genetic defects.

H350 May cause cancer.

(Contd. on page 8)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 602

(Contd. of page 7)

· Department issuing SDS: Quality Assurance & Environment Departement

· Contact: Chemist / Mohamed Khalil

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 1B: Carcinogenicity - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1