

Page 1/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 27.03.2023

Revision: 27.03.2023

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

• Trade name: Kapci 620

- Article number: 620
- *Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.*
- Application of the substance / the mixture .

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Kapci Coatings Industrial Zone El - Raswa Port Said EGYPT mohamed.khalil@kapci.com

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +20 66 3770000

2 Hazards identification

· Classification of the substance or mixture

• Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour. Skin Irrit. 2 H315 Causes skin irritation.

· Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms



Signal word Warning
 Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

· Precautionary statements

| 1 recumona | y statements |
|------------|--|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P103 | Read label before use. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P240 | Ground and bond container and receiving equipment. |
| | |

(Contd. on page 2)

GB

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 620

| | (Contd. of page 1) |
|---------------------|---|
| P241 | Use explosion-proof [electrical/ventilating/lighting] equipment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P303+P361+P353 | ³ IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P501 | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| • Other hazards | |
| · Results of PBT an | d vPvB assessment |
| • PBT: Not applicab | ole. |

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| CAS: 108-65-6 | Methoxypropylacetate | 2.5-10% |
|---|---|---------|
| EINECS: 203-603-9 | Flam. Liq. 3, H226 | 1 |
| Reg.nr.: 01-2119475791-29-0000 | | |
| 01-2119475791-29-XXXX | | |
| CAS: 123-86-4 | N-Butyl acetate | 2.5-10% |
| EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-0002 | Flam. Liq. 3, H226; STOT SE 3, H336 | - |
| CAS: 1330-20-7 | Xylene | 2.5-10% |
| EINECS: 215-535-7 | Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; | 1 |
| Reg.nr.: 01-2119488216-32 | Skin Irrit. 2, H315 | |
| 01-2119486136-34-XXXX | | |
| 0 | | |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed Breathing difficulty
- · Indication of any immediate medical attention and special treatment needed
- $No\ further\ relevant\ information\ available.$

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 3)

GB

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 620

(Contd. of page 2)

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Do not flush with water or aqueous cleansing agents
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see section 7.

· Control parameters

| WEL . | Short-term value: 548 mg/m³, 100 ppm | |
|--------|---|--|
| | Long-term value: 274 mg/m ³ , 50 ppm | |
| 1 | Sk | |
| 123-80 | 5-4 N-Butyl acetate | |
| WEL . | Short-term value: 966 mg/m³, 200 ppm | |
| | Long-term value: 724 mg/m³, 150 ppm | |
| 1330-2 | 20-7 Xylene | |
| WEL . | Short-term value: 441 mg/m³, 100 ppm | |
| | Long-term value: 220 mg/m ³ , 50 ppm | |
| , i | Sk; BMGV | |
| Ingrea | lients with biological limit values: | |
| 1330-2 | 20-7 Xylene | |
| BMGV | 650 mmol/mol creatinine | |
| | Medium: urine | |
| | Sampling time: post shift | |
| | Parameter: methyl hippuric acid | |
| Exnos | ure controls | |
| | | |

1 11

(Contd. on page 4)

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 620

· Protection of hands:

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

| Information on basic physical and chem. General Information | icai properties |
|--|---|
| Appearance: | |
| Form: | Fluid |
| Colour: | According to product specification |
| Odour: | <i>Characteristic</i> |
| Odour threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range: | 124 °C |
| Flash point: | 27 °C |
| Flammability (solid, gas): | Flammable. |
| Auto-ignition temperature: | 333 °C |
| Decomposition temperature: | Not determined. |
| Ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosive air vapour mixtures are possible. |
| Explosion limits: | |
| Lower: | 1.1 Vol % |
| Upper: | 7.5 Vol % |
| Vapour pressure at 20 °C: | 10.7 hPa |
| Density: | Not determined. |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not determined. |
| Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 620

| | (Contd. of page 4 |
|---|--|
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 30.0 % |
| VOC (EC) | 30.00 % |
| Solids content: | 70.0 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 Xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.

(Contd. on page 6)

GB

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 620

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| UN-Number | |
|---|---|
| ADR, IMDG, IATA | UN1263 |
| UN proper shipping name | |
| ADR | 1263 PAINT RELATED MATERIAL |
| IMDG, IATA | PAINT RELATED MATERIAL |
| Transport hazard class(es) | |
| ADR, IMDG, IATA | |
| | |
| Class | 3 Flammable liquids. |
| Label | 3 |
| Packing group | |
| ADR, IMDG, IATA | III |
| Environmental hazards: | Not applicable. |
| Special precautions for user | Warning: Flammable liquids. |
| Hazard identification number (Kemler code): | 30 |
| EMS Number: | <i>F-E</i> , <u><i>S-E</i></u> |
| Stowage Category | Α |
| Transport in bulk according to Annex II of Mary | |
| and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| ADR | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| Transport category | 3 |
| Tunnel restriction code | D/E |

(Contd. of page 5)

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 620

| | (Contd. of page 6) |
|--|--|
| · IMDG · Limited quantities (LQ) | 5L |
| \cdot Excepted quantities (\widetilde{EQ}) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · UN ''Model Regulation'': | UN 1263 PAINT RELATED MATERIAL, 3, III |

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.

· Department issuing SDS: Quality Assurance & Environment Departement

• Contact: Chemist / Mohamed Khalil • Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

[·] Directive 2012/18/EU