

Page 1/8

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 27.03.2023

Revision: 27.03.2023

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Kapci 630

• Article number: 630

- *Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.*
- Application of the substance / the mixture .

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier:

Kapci Coatings Industrial Zone El - Raswa Port Said EGYPT mohamed.khalil@kapci.com

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +20 66 3770000

2 Hazards identification

· Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation. • Hazard pictograms



· Signal word Danger

- Hazard-determining components of labelling: toluene
- · Hazard statements
- H225 Highly flammable liquid and vapour.H315 Causes skin irritation.H361d Suspected of damaging the unborn child.

(Contd. on page 2)

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 630

	(Contd. of page 1)	
H373 May cause	damage to organs through prolonged or repeated exposure.	
H304 May be fate	I if swallowed and enters airways.	
· Precautionary stat	ements	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read label before use.	
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.	
P321	Specific treatment (see on this label).	
P331	Do NOT induce vomiting.	
P303+P361+P353	¹ IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	
• Other hazards		

• Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 108-88-3	toluene	2.5-10%
EINECS: 203-625-9	Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp.	
Reg.nr.: 01-2119471310-51-0036	Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 1330-20-7	Xylene	2.5-10%
EINECS: 215-535-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332;	
Reg.nr.: 01-2119488216-32	Skin Irrit. 2, H315	
01-2119486136-34-XXXX		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed Breathing difficulty
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 3)

GB

Printing date 27.03.2023

Revision: 27.03.2023

(Contd. of page 2)

Trade name: Kapci 630

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see section 7.

· Control parameters

• Ingredients with limit values that require	monitoring at the workplace:
--	------------------------------

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm

Long-term value: 191 mg/m³, 50 ppm Sk

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

(Contd. on page 4)

GB

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 630

		(Contd. of page 3)
Ingred	ients with biological lin	
1330-2	0-7 Xylene	
	650 mmol/mol creatin Medium: urine Sampling time: post si Parameter: methyl hij	hift
Person Genera Keep a Immed Wash H Avoid o Respire In case use sel Protect The glo Due to the che Selectri degrad Materi The sel and va resista: applico Penetri The exi observe	are controls bal protective equipment of protective and hygien way from foodstuffs, be iately remove all soiled ands before breaks and contact with the skin. contact with the eyes and atory protection: e of brief exposure or lo f-contained respiratory tion of hands: Protective gloves we material has to be in missing tests no recom- emical mixture. ion of the glove material al of gloves lection of the suitable g vries from manufacture nce of the glove material ation. ation time of glove material ation time of glove material act break through time	 ti: mic measures: everages and feed. and contaminated clothing d at the end of work. ad skin. we pollution use respiratory filter device. In case of intensive or longer exposure protective device.
		~
Physi	cal and chemical p	roperties
		l and chemical properties
Gonori	al Information	
		Fluid
Appear		I'IIIII
Appear Form		According to product specification
Appear	ur:	According to product specification Characteristic

Not determined.

· pH-value:

· Change in condition

Melting point/freezing point: Undetermined.

(Contd. on page 5)

GB

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 630

Initial boiling point and boiling range	(Contd. of page 4
Flash point:	4 °C
Flammability (solid, gas):	Highly flammable.
Auto-ignition temperature:	500 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
Vapour pressure at 20 °C:	29 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	20.0 %
VÕC (EC)	20.00 %
Solids content:	80.0 %
Other information	No further relevant information available.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- \cdot Conditions to avoid No further relevant information available.
- $\cdot \textit{Incompatible materials:} No further relevant information available.$
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 Xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

(Contd. on page 6)

GB

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 630

- · Primary irritant effect:
- *Skin corrosion/irritation Causes skin irritation.*
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity
- Suspected of damaging the unborn child.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard
- May be fatal if swallowed and enters airways.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- \cdot Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· ADR, IMDG, IATA	UN1263	
· UN proper shipping name		
$\cdot ADR$	1263 PAINT RELATED MATERIAL	
· IMDG, IATA	PAINT RELATED MATERIAL	

(Contd. of page 5)

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 630

	(Contd. of page
· Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· Packing group · ADR, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
 Special precautions for user Hazard identification number (Kemler code): EMS Number: 	Warning: Flammable liquids. 33 F-E,S-E
· EMS Number: · Stowage Category	B
• Transport in bulk according to Annex II of Mary and the IBC Code	pol Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
• Transport category • Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1263 PAINT RELATED MATERIAL, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

(Contd. on page 8)

GB

GB

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 630

(Contd. of page 7)
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
· Department issuing SDS: Quality Assurance & Environment Departement
· Contact: Chemist / Mohamed Khalil
· Abbreviations and acronyms:
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the
International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Lig. 2: Flammable liquids – Category 2
Flam. Lig. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1