

Page 1/8

# Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 27.03.2023

Revision: 27.03.2023

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Kapci 651

- Article number: 651
- *Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.*
- Application of the substance / the mixture .

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Kapci Coatings Industrial Zone El - Raswa Port Said EGYPT mohamed.khalil@kapci.com

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +20 66 3770000

## **2** Hazards identification

· Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. • Hazard pictograms



· Signal word Warning

• *Hazard-determining components of labelling: N-Butyl acetate* 

- · Hazard statements
- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- · Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

GB

Printing date 27.03.2023

Revision: 27.03.2023

#### Trade name: Kapci 651

	(Contd. of page 1)
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353	<sup>3</sup> <i>IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].</i>
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	
Results of PBT an	d vPvB assessment

· **PBT:** Not applicable.

• **vPvB:** Not applicable.

## **3** Composition/information on ingredients

### · Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:	
-------------------------	--

· Dangerous components:		
CAS: 1330-20-7	Xylene	25-50%
EINECS: 215-535-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332;	
Reg.nr.: 01-2119488216-32	Skin Irrit. 2, H315	
01-2119486136-34-XXXX		
CAS: 123-86-4	N-Butyl acetate	10-25%
EINECS: 204-658-1	Flam. Liq. 3, H226; STOT SE 3, H336	1
Reg.nr.: 01-2119485493-29-0002		
CAS: 108-65-6	Methoxypropylacetate	2.5-10%
EINECS: 203-603-9	Flam. Liq. 3, H226	
Reg.nr.: 01-2119475791-29-0000		
01-2119475791-29-XXXX		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

### 4 First aid measures

### · Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- In case of unconsciousness place patient stably in side position for transportation.
- $\cdot$  After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed Breathing difficulty
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

GB

Printing date 27.03.2023

Revision: 27.03.2023

(Contd. of page 2)

#### Trade name: Kapci 651

**5** Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### **6** Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- $\cdot \textit{Environmental precautions: } Do not allow to enter sewers/ surface or ground water.$
- $\cdot$  Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
   Information about fire - and explosion protection:
- *Keep ignition sources away Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see section 7.

· Control parameters

 • Ingredients with limit values that require monitoring at the workplace:

 1330-20-7 Xylene

 WEL
 Short-term value: 441 mg/m³, 100 ppm<br/>Long-term value: 220 mg/m³, 50 ppm<br/>Sk; BMGV

 123-86-4 N-Butyl acetate

 WEL
 Short-term value: 966 mg/m³, 200 ppm<br/>Long-term value: 724 mg/m³, 150 ppm

 (Contd. on page 4)

Printing date 27.03.2023

Revision: 27.03.2023

### Trade name: Kapci 651

(Contd. of page	3)
108-65-6 Methoxypropylacetate	
WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm	
Sk	
	4
· Ingredients with biological limit values:	_
1330-20-7 Xylene	_
BMGV 650 mmol/mol creatinine Medium: urine	
Sampling time: post shift	
Parameter: methyl hippuric acid	
Exposure controls	
• Personal protective equipment: • General protective and hygienic measures:	
Keep away from foodstuffs, beverages and feed.	
Immediately remove all soiled and contaminated clothing	
Wash hands before breaks and at the end of work.	
Avoid contact with the skin.	
Avoid contact with the eyes and skin.	
· Respiratory protection:	
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure	re
use self-contained respiratory protective device. • <b>Protection of hands:</b>	
Thechon of names.	
Protective gloves	
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation the chemical mixture.	n/
Selection of the glove material on consideration of the penetration times, rates of diffusion and the	ıe
degradation	
· Material of gloves	
The selection of the suitable gloves does not only depend on the material, but also on further marks of quali and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the	
resistance of the glove material can not be calculated in advance and has therefore to be checked prior to th application.	ıe
· Penetration time of glove material	
The exact break through time has to be found out by the manufacturer of the protective gloves and has to l	)e
observed.	
· Eye protection:	
Tightly sealed goggles	
9 Physical and chemical properties	
Information on basic physical and chemical properties	
• General Information • Appearance:	

Appearance:Form:FluidColour:According to product specificationOdour:Characteristic

(Contd. on page 5)

GB

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 651

Odour threshold:	(Contd. of page Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point: Initial boiling point and boiling range	Undetermined.
Flash point:	27 °C
Flammability (solid, gas):	Flammable.
Auto-ignition temperature:	333 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	Nat miasihla an difficult to min
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	85.0 % 85.00 %
VOC (EC)	
Solids content:	15.0 %
Other information	No further relevant information available.

### **10 Stability and reactivity**

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### **11 Toxicological information**

· Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

GB

GB

# Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 27.03.2023

Revision: 27.03.2023

# Trade name: Kapci 651

I D/I C	(Contd.
	50 values relevant for classification:
1330-2	0-7 Xylene
Oral	LD50 4,300 mg/kg (rat)
Derma	LD50 2,000 mg/kg (rabbit)
Primar	y irritant effect:
	rrosion/irritation
Causes	skin irritation.
	eye damage/irritation Based on available data, the classification criteria are not met.
	tory or skin sensitisation Based on available data, the classification criteria are not met.
	nal toxicological information:
	ffects (carcinogenity, mutagenicity and toxicity for reproduction)
	ell mutagenicity Based on available data, the classification criteria are not met.
	ogenicity Based on available data, the classification criteria are not met. <b>uctive toxicity</b> Based on available data, the classification criteria are not met.
	single exposure
	use drowsiness or dizziness.
	repeated exposure Based on available data, the classification criteria are not met.
	ion hazard Based on available data, the classification criteria are not met.
<b>Mobili</b> Additio Genero Water Do not	umulative potential No further relevant information available. y in soil No further relevant information available. nal ecological information: l notes:
Results PBT: 1	nazard class 2 (German Regulation) (Self-assessment): hazardous for water allow product to reach ground water, water course or sewage system. • to drinking water if even small quantities leak into the ground. • of PBT and vPvB assessment Vot applicable. Not applicable.
Results PBT: 1 vPvB: 0 Other o	allow product to reach ground water, water course or sewage system. to drinking water if even small quantities leak into the ground. <b>of PBT and vPvB assessment</b> Not applicable. Not applicable. <b>adverse effects</b> No further relevant information available.
Results PBT: 1 vPvB: Other o	allow product to reach ground water, water course or sewage system. • to drinking water if even small quantities leak into the ground. • of PBT and vPvB assessment Vot applicable. Not applicable.
Results PBT: 1 vPvB: Other o Dispo Waste Recom	allow product to reach ground water, water course or sewage system. to drinking water if even small quantities leak into the ground. <b>of PBT and vPvB assessment</b> Not applicable. Not applicable. <b>adverse effects</b> No further relevant information available.

· UN-Number · ADR, IMDG, IATA	UN1263
· UN proper shipping name	
$\cdot ADR$	1263 PAINT RELATED MATERIAL
· IMDG, IATA	PAINT RELATED MATERIAL

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 651

	(Contd. of page
· Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· Packing group · ADR, IMDG, IATA	111
• Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids.
• Hazard identification number (Kemler code):	30
· EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
· Stowage Category	A
• Transport in bulk according to Annex II of Marg and the IBC Code	pol Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml
• Transport category • Tunnel restriction code	Maximum net quantity per outer packaging: 1000 ml 3 D/E
· IMDG	
· Limited quantities (LQ)	5L
$\cdot$ Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN 1263 PAINT RELATED MATERIAL, 3, III

## **15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

 $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

 $\cdot$  Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation.

(Contd. on page 8)

GB

Printing date 27.03.2023

Revision: 27.03.2023

#### Trade name: Kapci 651

(Contd. of page 7) H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. · Department issuing SDS: Quality Assurance & Environment Departement · Contact: Chemist / Mohamed Khalil · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3