

Page 1/8

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 27.03.2023 Revision: 27.03.2023

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Kapci 664
- · Article number: 664
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture .
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kapci Coatings

Industrial Zone El - Raswa

Port Said

EGYPT

mohamed.khalil@kapci.com

- · Further information obtainable from: Product safety department
- · Emergency telephone number: During normal opening times: +20 66 3770000

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

502 GHS0'

- · Signal word Warning
- · Hazard-determining components of labelling:

N-Butyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 664

(Contd. of page 1) P102 Keep out of reach of children.

P103 Read label before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

smoking.

Use explosion-proof [electrical/ventilating/lighting] equipment. P241

Avoid breathing dust/fume/gas/mist/vapours/spray. P261

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 108-65-6	Methoxypropylacetate	10-25%
EINECS: 203-603-9	Flam. Liq. 3, H226	
Reg.nr.: 01-2119475791-29-0000		
01-2119475791-29-XXXX		
CAS: 123-86-4	N-Butyl acetate	10-25%
EINECS: 204-658-1	Flam. Liq. 3, H226; STOT SE 3, H336	
Reg.nr.: 01-2119485493-29-0002	•	
CAS: 1330-20-7	Xylene	10-25%
EINECS: 215-535-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332;	
Reg.nr.: 01-2119488216-32	Skin Irrit. 2, H315	
01-2119486136-34-XXXX		

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Breathing difficulty
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 664

(Contd. of page 2)

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-65-6 Methoxypropylacetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

123-86-4 N-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 4)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 664

(Contd. of page 3)

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic

(Contd. on page 5)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 664

	(Contd. of page	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. v: 124 °C	
· Flash point:	27 °C	
Flammability (solid, gas):	Flammable.	
· Auto-ignition temperature:	333 °C	
Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive. However, formation of explosive ai vapour mixtures are possible.	
· Explosion limits: Lower: Upper:	1.1 Vol % 7.5 Vol %	
· Vapour pressure at 20 °C:	10.7 hPa	
· Density: · Relative density · Vapour density · Evaporation rate	Not determined. Not determined. Not determined. Not determined.	
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
· Solvent content: Organic solvents: VOC (EC)	75.0 % 75.00 %	
Solids content:	25.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 664

(Contd. of page 5)

· LD/LC50 values relevant for classific

1330-20-7 Xylene

 Oral
 LD50
 4,300 mg/kg (rat)

 Dermal
 LD50
 2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Trans	port inj	tormai	ton
----------	----------	--------	-----

· UN-Number

· ADR, IMDG, IATA UN1263

· UN proper shipping name

· ADR 1263 PAINT
· IMDG, IATA PAINT

(Contd. on page 7)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 664

	(Contd. of pa	
Transport hazard class(es)		
ADR, IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	
Packing group ADR, IMDG, IATA	III	
Environmental hazards:	Not applicable.	
Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (Kemler code):	30	
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>	
Stowage Category	A	
Transport in bulk according to Annex II of Marq and the IBC Code	r pol Not applicable.	
Transport/Additional information:		
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml	
Transport category Tunnel restriction code	Maximum nei quantity per outer packaging. 1000 mt 3 D/E	
IMDG		
Limited quantities (LQ)	5L	
Excepted quantities (EQ)	Code: E1	
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml	
UN "Model Regulation":	UN 1263 PAINT, 3, III	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

(Contd. on page 8)

Printing date 27.03.2023 Revision: 27.03.2023

Trade name: Kapci 664

(Contd. of page 7)

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Quality Assurance & Environment Departement
- · Contact: Chemist / Mohamed Khalil
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3