

Page 1/8

## Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 27.03.2023

Revision: 27.03.2023

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Kapci 800

- Article number: 800
- *Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.*
- · Application of the substance / the mixture .

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Kapci Coatings Industrial Zone El - Raswa Port Said EGYPT mohamed.khalil@kapci.com

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +20 66 3770000

## **2** Hazards identification

· Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

· Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. • Hazard pictograms



· Signal word Danger

P101

 Hazard-determining components of labelling: butanol
 Hazard statements

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- · Precautionary statements

If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Printing date 27.03.2023

Revision: 27.03.2023

### Trade name: Kapci 800

	(Contd. of page 1)
P102	Keep out of reach of children.
P103	Read label before use.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with
	water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
Other hazards	
Results of PBT and	l vPvB assessment

· **PBT:** Not applicable.

• **vPvB:** Not applicable.

## **3** Composition/information on ingredients

### · Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:		
CAS: 67-63-0	propan-2-ol	2.5-10%
EINECS: 200-661-7	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 78-83-1	butanol	2.5-10%
EINECS: 201-148-0	Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 1330-20-7	Xylene	2.5-10%
EINECS: 215-535-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332;	
Reg.nr.: 01-2119488216-32	Skin Irrit. 2, H315	
01-2119486136-34-XXXX		
CAS: 123-86-4	N-Butyl acetate	≤2.5%
EINECS: 204-658-1	Flam. Liq. 3, H226; STOT SE 3, H336	1
Reg.nr.: 01-2119485493-29-0002		
CAS: 141-78-6	ethyl acetate	≤2.5%
EINECS: 205-500-4	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119475103-46		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

## 4 First aid measures

· Description of first aid measures

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.

• Information for doctor:

- $\cdot \textit{Most important symptoms and effects, both acute and delayed} \textit{ Breathing difficulty}$
- $\cdot$  Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

Printing date 27.03.2023

Revision: 27.03.2023

(Contd. of page 2)

### Trade name: Kapci 800

**5** Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### **6** Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### 7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see section 7.

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm Long-term value: 999 mg/m<sup>3</sup>, 400 ppm

(Contd. on page 4)

Printing date 27.03.2023

Revision: 27.03.2023

### Trade name: Kapci 800

	(Contd. of page 3)	
78-83	2-1 butanol	
WEL	Short-term value: 231 mg/m <sup>3</sup> , 75 ppm	
	Long-term value: 154 mg/m <sup>3</sup> , 50 ppm	
1330-	20-7 Xylene	
WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm	
	Long-term value: 220 mg/m <sup>3</sup> , 50 ppm	
	Sk; BMGV	
123-86-4 N-Butyl acetate		
WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm	
	Long-term value: 724 mg/m <sup>3</sup> , 150 ppm	
141-7	8-6 ethyl acetate	
WEL	WEL Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm	
	Long-term value: 734 mg/m³, 200 ppm	
· Ingre	dients with biological limit values:	
1330-	20-7 Xylene	
BMG	V 650 mmol/mol creatinine	
	Medium: urine	
	Sampling time: post shift	
	Parameter: methyl hippuric acid	
	·	

### · Exposure controls

· Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Printing date 27.03.2023

Revision: 27.03.2023

	(Contd. of page
· Eye protection:	(cond. of page
Tightly sealed goggles	
Physical and chemical properties	
· Information on basic physical and chem	ical properties
· General Information	
· Appearance: Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	
· Flash point:	13 °C
· Flammability (solid, gas):	Highly flammable.
• Auto-ignition temperature:	390 °C
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive ai
	vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol % 12 Vol %
Upper:	
• Vapour pressure at 20 °C:	43 hPa
· Density:	Not determined.
· Relative density	Not determined. Not determined.
• Vapour density • Evaporation rate	Not determined.
• Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	35.0 %
VOC (EC)	35.00 %
Solids content:	65.0 %
• Other information	No further relevant information available.

(Contd. on page 6)

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 800

(Contd. of page 5)

## **10 Stability and reactivity**

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- *Conditions to avoid* No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

#### 1330-20-7 Xylene

*Oral LD50 4,300 mg/kg (rat)* 

Dermal LD50 2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- $\cdot$  Serious eye damage/irritation
- Causes serious eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **12** Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- *Persistence and degradability* No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 7)

Printing date 27.03.2023

Revision: 27.03.2023

Trade name: Kapci 800

(Contd. of page 6)

## **13 Disposal considerations**

· Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

# 14 Transport information

· UN-Number · ADR, IMDG, IATA	UN1263
	011205
· UN proper shipping name · ADR · IMDG, IATA	1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
· Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· Packing group · ADR, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
<ul> <li>Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
• Transport in bulk according to Annex II of Mary and the IBC Code	<b>pol</b> Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml
· Transport category	Maximum net quantity per outer packaging: 500 ml 2
• Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	IL G. L. F2
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II

(Contd. on page 8)

GB

Printing date 27.03.2023

Revision: 27.03.2023

### Trade name: Kapci 800

(Contd. of page 7)

## **15 Regulatory information**

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. · Department issuing SDS: Quality Assurance & Environment Departement · Contact: Chemist / Mohamed Khalil · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3