

Page 1/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 25.03.2023 Revision: 25.03.2023

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Kapci KRMO 100/60 WS
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture .
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kapci Coatings Industrial Zone El - Raswa Port Said

EGYPT

mohamed.khalil@kapci.com

- · Further information obtainable from: Product safety department
- · Emergency telephone number: During normal opening times: +20 66 3770000

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

- · Signal word Danger
- · Hazard-determining components of labelling:

Solvent naphtha (petroleum), medium aliph.

· Hazard statements

H226 Flammable liquid and vapour.

H372 Causes damage to the central nervous system through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 25.03.2023 Revision: 25.03.2023

Trade name: Kapci KRMO 100/60 WS

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Other hazards

· Results of PBT and vPvB assessment

· *PBT*: Not applicable. · *vPvB*: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-88-7	Solvent naphtha (petroleum), medium aliph.	25-50%
EINECS: 265-191-7	Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332	
CAS: 1330-20-7	Xylene	2.5-10%
EINECS: 215-535-7	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin	
Reg.nr.: 01-2119488216-32	Irrit. 2, Ĥ315	
01-2119486136-34-		
XXXX		

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Breathing difficulty
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 25.03.2023 Revision: 25.03.2023

Trade name: Kapci KRMO 100/60 WS

(Contd. of page 2)

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 4)

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 25.03.2023 Revision: 25.03.2023

Trade name: Kapci KRMO 100/60 WS

(Contd. of page 3)

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 F nysicai ana chemicai properties				
· Information on basic physical and chemical properties				
· General Information				

· Appearance:

Form: Fluid

Colour: According to product specification

Characteristic · Odour: · Odour threshold: Not determined. Not determined.

· pH-value:

· Change in condition

· Vapour pressure at 20 °C:

· Density at 20 °C: · Relative density

· Vapour density

Melting point/freezing point: Undetermined. Initial hoiling point and hoiling range: 153-198 °C

Thural bouing point and bouing range: 133-196 C		
· Flash point:	41 °C	
· Flammability (solid, gas):	Flammable.	
\cdot $Auto$ -ignition temperature:	265 °C	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Explosion limits:		
Lower:	0.6 Vol %	
Upper:	6.5 Vol %	

6.6 hPa 0.7944 g/cm^3

Not determined.

Not determined.

(Contd. on page 5)

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 25.03.2023 Revision: 25.03.2023

Trade name: Kapci KRMO 100/60 WS

	(Contd. of page
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents: VOC (EC)	40.0 % 40.00 %
Solids content:	60.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LI	ノノ上しろひ	vaiues	reievani	jor	ciassij	ісаноп:	
------	--------	--------	----------	-----	---------	---------	--

ED/LC30 values relevant for classification.		
64742-88-7 Solvent naphtha (petroleum), medium aliph.		
Oral	LD50	>6,500 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)
Inhalative	LC50/4 h	>14 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

Causes damage to the central nervous system through prolonged or repeated exposure.

· Aspiration hazard

May be fatal if swallowed and enters airways.

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 25.03.2023 Revision: 25.03.2023

Trade name: Kapci KRMO 100/60 WS

(Contd. of page 5)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

14 Transport information

· Stowage Category

and the IBC Code

· Transport in bulk according to Annex II of Marpol

• **Recommendation:** Disposal must be made according to official regulations.

· UN-Number · ADR, IMDG, IATA	UN1866	
· UN proper shipping name		
ADR	1866 RESIN SOLUTION	
· IMDG, IATA	RESIN SOLUTION	
· Transport hazard class(es)		
ADR, IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	
Packing group		
ADR, IMDG, IATA	III	
Environmental hazards:	Not applicable.	
Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (Kemler code):	30	
EMS Number:	F- E , S - E	

Not applicable.

(Contd. on page 7)

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 25.03.2023 Revision: 25.03.2023

Trade name: Kapci KRMO 100/60 WS

Transport/Additional information:	(Contd. of pa
· ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
~ ~	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN ''Model Regulation'':	UN 1866 RESIN SOLUTION, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

- · Department issuing SDS: Quality Assurance & Environment Departement
- · Contact: Chemist / Mohamed Khalil
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard - Category 1