

Page 1/8

## Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 30.03.2023

Revision: 30.03.2023

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Kapci WS 690

- · Article number: WS 690
- *Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.*
- · Application of the substance / the mixture .

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Kapci Coatings Industrial Zone El - Raswa Port Said EGYPT mohamed.khalil@kapci.com

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +20 66 3770000

### **2** Hazards identification

• Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

*Repr.* 2 *H361d Suspected of damaging the unborn child.* 

- STOT SE 3 H336 May cause drowsiness or dizziness.
- STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



· Signal word Danger

- Hazard-determining components of labelling: toluene
- N-Butyl acetate
- · Hazard statements
- H225 Highly flammable liquid and vapour.

(Contd. on page 2)

Printing date 30.03.2023

Revision: 30.03.2023

#### Trade name: Kapci WS 690

(Contd. of page 1)	
315 Causes skin irritation.	
361d Suspected of damaging the unborn child.	
336 May cause drowsiness or dizziness.	
373 May cause damage to organs through prolonged or repeated exposure.	
304 May be fatal if swallowed and enters airways.	
recautionary statements	
101 If medical advice is needed, have product container or label at hand.	
102 Keep out of reach of children.	
103 Read label before use.	
<i>301+P310</i> IF SWALLOWED: Immediately call a POISON CENTER/ doctor.	
321 Specific treatment (see on this label).	
<i>Do NOT induce vomiting.</i>	
303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with	
water [or shower].	
<i>Take off contaminated clothing and wash it before reuse. Take off contaminated clothing and wash it before reuse.</i>	
405 Store locked up.	
501 Dispose of contents/container in accordance with local/regional/national/international	
regulations.	
ther hazards	
esults of PBT and vPvB assessment	

• **PBT:** Not applicable.

· vPvB: Not applicable.

### **3** Composition/information on ingredients

#### · Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-0036	toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	10-25%		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-0002	N-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	10-25%		
CAS: 111-76-2 EINECS: 203-905-0	2-butoxyethanol Acute Tox. 3, H311; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-10%		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First aid measures

 $\cdot$  Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:

· Most important symptoms and effects, both acute and delayed Breathing difficulty

- $\cdot$  Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

GB

Printing date 30.03.2023

Revision: 30.03.2023

(Contd. of page 2)

#### Trade name: Kapci WS 690

**5** Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### **6** Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- $\cdot$  Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- Reference to other sections
  See Section 7 for information on safe handling.
  See Section 8 for information on personal protection equipment.
  See Section 13 for disposal information.

## 7 Handling and storage

#### · Handling:

- *Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.*
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- $\cdot$  Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see section 7.

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

Sk

WEL Short-term value: 384 mg/m<sup>3</sup>, 100 ppm

Long-term value: 191 mg/m<sup>3</sup>, 50 ppm

(Contd. on page 4)

GB

Printing date 30.03.2023

Revision: 30.03.2023

#### Trade name: Kapci WS 690

	(Contd. of page 3)
123-8	6-4 N-Butyl acetate
WEL	Short-term value: 966 mg/m³, 200 ppm
	Long-term value: 724 mg/m³, 150 ppm
111-7	6-2 2-butoxyethanol
WEL	Short-term value: 246 mg/m³, 50 ppm
	Long-term value: 123 mg/m <sup>3</sup> , 25 ppm
	Sk, BMGV
· Ingre	dients with biological limit values:
111-7	6-2 2-butoxyethanol
BMG	V 240 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: butoxyacetic acid

#### · Exposure controls

#### · Personal protective equipment:

- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

(Contd. on page 5)

Printing date 30.03.2023

Revision: 30.03.2023

#### Trade name: Kapci WS 690

(Contd. of page 4)

9 Physical and chemical properties	
· Information on basic physical and chem	ical properties
• General Information	
· Appearance:	
Form:	Fluid
Colour: • Odour:	According to product specification Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	110-111 °C
· Flash point:	4 °C
· Flammability (solid, gas):	Highly flammable.
• Auto-ignition temperature:	240 °C
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	29 hPa
• Vapour pressure at 50 •C:	124 hPa
· Density at 20 •C:	0.87778 g/cm <sup>3</sup>
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	45.0 %
VOC (EC)	45.00 %
Solids content:	55.0 %
· Other information	No further relevant information available.

# **10 Stability and reactivity**

· Reactivity No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)

Printing date 30.03.2023

Revision: 30.03.2023

Trade name: Kapci WS 690

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

### **11 Toxicological information**

· Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

#### 111-76-2 2-butoxyethanol

Oral LD50 1,200 mg/kg (ATE) 1,480 mg/kg (rat)

Dermal LD50 400 mg/kg (rab)

- Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity
- Suspected of damaging the unborn child.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard
- May be fatal if swallowed and enters airways.

### **12 Ecological information**

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 30.03.2023

Revision: 30.03.2023

(Contd. of page 6)

Trade name: Kapci WS 690

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number ADR, IMDG, IATA	UN1263
UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
Transport hazard class(es)	
ADR, IMDG, IATA	
	2 El anno abba lina i da
Class Label	3 Flammable liquids. 3
Packing group ADR, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
Transport in bulk according to Annex II of Marg and the IBC Code	ool Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	2 D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN ''Model Regulation'':	UN 1263 PAINT, 3, II

# **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

 $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 8)

GB

Printing date 30.03.2023

Revision: 30.03.2023

Trade name: Kapci WS 690

(Contd. of page 7) • Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t · Chemical safety assessment: A Chemical Safety Assessment has not been carried out. **16 Other information** This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. · Relevant phrases H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. · Department issuing SDS: Quality Assurance & Environment Departement · Contact: Chemist / Mohamed Khalil · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 3: Acute toxicity - Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1