

Latico Hardeners

Product description

Latico Hardeners are polyisocyanate based hardeners for 2K products. They are especially designed for Latico 2K acrylic paints, Latico MS and HS clearcoats, Latico 2K MS and HS fillers, and Latico 2K sealers. Having more kind of hardeners means that all painting conditions can be optimized and reliable application can be achieved.

Products

EXTRA FAST ARDENERS		
FAST ARDENERS		
Latico 5610	Suitable for partial and medium size respray at low temperature.	See Technical Data Sheet for Base Products
NORMAL HARDENERS		
Latico 5600	Suitable for partial and complete respray at normal temperature.	See Technical Data Sheet for Base Products
Latico 5955	Suitable for partial and complete respray at normal temperature.	See Technical Data Sheet for Base Products
Latico 5455	Used for filler Latico 5450, Suitable for partial and complete respray at normal temperature.	See Technical Data Sheet for Base Products
SLOW HARDENERS		
Latico 5620	Suitable for partial and complete respray at high temperature.	See Technical Data Sheet for Base Products

Choice of hardeners

The recommendations below are for guidance only. Please refer to the TDS of the respective 2K products for more detailed information about the selection of the hardeners.

HARDENERS	FAST	NORMAL	SLOW
	Latico 5610	Latico 5600/Latico5955	Latico 5620
Complete respray	Unsuitable	Suitable	Suitable
Partial respray	Suitable	Suitable	Not particularly suitable
15°C- 20°C	Suitable	Suitable	Unsuitable
20°C- 25°C	Suitable	Suitable	Not particularly suitable
> 30°C	Not particularly suitable	Not particularly suitable	Suitable
> 35°C	Unsuitable	Unsuitable	Suitable

General notes

1. Seal container immediately after use.
2. Do NOT store hardeners in dump conditions.

Health and Safety

1. For full Health and Safety information please refer to Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.