



KAPCI
COATINGS

Technical Data Sheet

Issue date January 2024

for professional use only

Kapci Tex 7010

Description

Kapci Tex 7010 is high quality decorative texture putty for interior and exterior surfaces. Kapci Tex 7010 is recommended for application over bricks, plaster, concrete and asbestos cement sheets.

Product Features:

Easy to apply

- High durability
- Excellent hiding power
- Excellent weathering resistance;
- Easily formed in different shapes depending on application method

Physical Properties:

Color:	White and colored
Viscosity	72±3 Poise
Solid content	70±3 %
Density	1.72±0.03gm/cm ³
Coverage	2-2.5 m ² /kg

Surface preparation

- Remove all loose, defective paint or powdery residues or dust.
- Repair cracks, uneven surfaces with a suitable fillers or surfacer.
- Smoothen the putty / filler areas with sand paper.
- Surfaces to be painted must be cleaned thoroughly and dry and free from contaminations, grease and other foreign matters.
- Avoid painting when the moisture content and alkalinity of the walls are still high.
- Apply Kapci Sealer 751 or Kapci Sealer 756 in one coat;
- Apply Kapci Tex 7010 in one coat according to desired finish effect.
- Apply Kapci Clear 752 in one coat;

Application


Tools for application

Roller	Brush
Recommended	Recommended to paint corners and edges.

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.



KAPCI COATINGS



Mixing Ratio

100% Kapci 7010 : 5% water



Drying time at 25 °C & 60% R.H

Initial drying time 2-3h

Recoating time 24h

Final drying time 24h

General Notes

1. Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.
2. Recommended data given is, for recoating with the same generic type of paint.
3. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.
4. The surface should be dry and free from any contamination prior to application of the subsequent coat.
5. Cleaner of application Tools is water

Shelf life and Storage

Two years from production date if stored in original sealed container at normal temperature. Keep away from direct sun light.

Health and Safety

1. For full Health and Safety information, refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.