



KAPCI
COATINGS

Technical Data Sheet

Issue date January 2024

for professional use only

Kapci Putty 750

Description

Kapci Putty 750 is waterborne putty based on vinyl-acrylic copolymer. It is used to eliminate surface imperfections over new and old, previously painted cement or plaster interior surfaces.

Product Features

- Easily applied;
- Excellent filling ability
- Excellent flow and leveling
- Easy to sand

Physical Properties

Color	White
Viscosity	Poise
Solid content	70±3 %
Density	1.72±0.03gm/cm ³
Coverage	2.5-3 m ² /kg

Substrates and surface preparation

Kapci Putty 750 is used for new and old cement or plaster interior surfaces. All new or already painted surfaces should be free from dust, grease and waxes.

Application

New cement and plaster surfaces

1. Apply Kapci Sealer 751 in one coat
2. Apply Kapci Putty 750 in two cross layers

Drying time at 25 °C & 60% R.H



Initial drying time 23h
Recoating time 24h
Final drying time 24h

Tools for application

Putty knife

Cleaner for application tools:

water

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.



KAPCI
COATINGS

Shelf life and Storage

Two years from production date if stored in original sealed container at normal temperature. Keep away from direct sun light.

Health and Safety

1. For full Health and Safety information, refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.