



KAPCI
COATINGS

Technical Data Sheet

Issue date January 2024

for professional use only

Kapci Sealer 751

Product Description

Kapci Sealer 751 is a priming coat based on modified acrylic resin, especially designed for application over concrete, cement, plaster, bricks and stones. It is used for surface pretreatment.

Products features

Chemically resistant to alkaline compounds;
Good impregnating ability
Easily applied
Fast drying
High coverage
Economic cost

Physical Properties

Color:	White after drying
Viscosity	18±3 Krebs
Solid content	44±3 %
Density	1.32±0.03gm/cm ³
Gloss	Matt
Coverage	16-20 m ² /kg (as ready for use product)

Substrate and surface preparation

Kapci Sealer 751 is recommended as a priming coat for cement and plaster surfaces to consolidate the superficial layer of such surfaces. It is used as a sealing coat to ensure excellent adhesion of a subsequent waterborne coating system. All new or already painted surfaces should be free from dust, grease and waxes.

Application

Apply Kapci Sealer 751 in one coat after dilution with water 50%, to reach the application viscosity. Apply Kapci Putty 750 or Kapci Putty 749 in two cross layers.

Drying time at 25 °C & 60% R.H



Initial drying time 1h
Final drying time 6h

Tools for application:

Brush or roller

Cleaner for application tools:

Water

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.



KAPCI
COATINGS

Shelf life and Storage:

Two years from production date if stored in original sealed container at normal temperature. Keep away from direct sun light.

Health and Safety

1. For full Health and Safety information, refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.