



KAPCI
COATINGS

Technical Data Sheet

Issue date January 2024

For professional use only

Kapci Clear 752

Product description

Kapci Clear 752 is waterborne transparent clear coat based on modified acrylic emulsion. It is recommended for both interior and exterior applications where high-quality finish is required.

Kapci Clear 752 is recommended for application over matt emulsion paints, masonry, bricks, plaster, concrete and cements sheets.

Product Features

Alkali resistant

- Washable
- Excellent non-yellowing properties
- Flexible to accommodate hair cracks in substrate

Physical Properties

Color:	Transparent
Viscosity	18 ±3 Krebs
Solid content	26 ±3 %
Density	0.98 ±0.03gm/cm ³
Gloss	High Gloss
Coverage	16-20 m ² /kg (as ready for use product)

Application

Tools for application

Roller	Brush	Spray
Recommended	Recommended to paint corners and edges.	Use airless spray or conventional spray.
		Guiding data for airless spray Nozzle tip 0.015–0.021" Spray angle degrees 20°-60° Pressure at nozzle 140 - 190 kg/cm ² (2100 psi)

Surface preparation

- **For new surface** Apply Kapci Sealer 751 in one coat; then apply Kapci Putty 750, then apply again 751
 - **For previously painted surfaces with alkyd paints** sand, remove dust then apply Super matt 766
 - **For previously painted surfaces with emulsion paints**, wash surface and apply Kapci Sealer 751
1. Apply suitable type of matt emulsion paint (Laticeo 737 or Kapci Coat 733) in two coats;

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.



KAPCI COATINGS

2. Apply Kapci Clear 752 in two coats after dilution with water 100%, to reach the suitable application viscosity;

Drying time at 25 °C & 60% R.H



Initial drying time	1h
Recoating time	4h
Final drying time	6h

General Notes

1. Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.
2. Recommended data given is, for recoating with the same generic type of paint.
3. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.
4. The surface should be dry and free from any contamination prior to application of the subsequent coat.
5. Cleaner of application Tools is water

Shelf Life and Storage

Two years from production date if stored in original sealed container at normal temperature. Keep away from direct sun light.

Health and Safety

1. For full Health and Safety information, refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.