



KAPCI
COATINGS

Technical Data Sheet

Issue date January 2024

for professional use only

Kapci Aqua Pearl 785

Product description

Kapci Aqua Pearl 785 is especially designed waterborne product that gives an attractive pearlescent decorative effect.

Product Features

- Easily applied
- Easily colored
- Weather resistance

Physical Properties

Color:	Silver, gold, bronze and maroon
Solid content:	48±3%
Density:	38±0.03gm/cm ³
Coverage:	10-12 m ² /kg

Substrates and surface preparation

Kapci Aqua Pearl 785 is recommended for application over plaster, wood, or cement surfaces. All new or previously painted surfaces should be free from dust, grease and waxes.

Application

1. Apply Kapci Sealer751 in one coat;
2. Apply Kapci Putty750 in two or three cross layers;
3. Surface sanding;
4. Apply Kapci Coat 730 in one or two coats;
5. Apply Kapci Super or Super Lux (tinted according to desirable finish) in one or two coats. Ensure smooth surface;
6. Apply Kapci Aqua Pearl 785 in one coat after dilution with water 30%-40%, to reach the application viscosity;

Drying time at 25 °C & 60% R.H



Initial drying time	2h
Recoating time	6h
Final drying time	24h

Tools for application:

Roller, sponge form or any application tool to give desired decorative effect.

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.



KAPCI
COATINGS

Cleaner for application Tools:

water

Shelf life and Storage

Two years from production date if stored in original sealed container at normal temperature. Keep away from direct sun light.

Health and Safety

1. For full Health and Safety information, refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.