



KAPCI
COATINGS

Technical Data Sheet

Issue date January 2024

for professional use only

Kapci Granulite 789

Description

Kapci Granulite 789 is specially designed product that gives an attractive granite appearance to surfaces.

Product Features

Easily applied;
High hardness;
Washable;
Weather resistance;

Physical Properties

Color	According to Kapci color chart
Solid content	45±3%
Density	0.99±0.03gm/cm ³
Coverage	4-5 m ² /kg

Substrate and surface preparation

- Kapci 789 is recommended for application over bricks, plaster, concrete and asbestos cement sheets.
- Remove all loose, defective paint or powdery residues or dust.
- Repair cracks, uneven surfaces with a suitable fillers or surfacer.
- Smoothen the putty / filler areas with sand paper.
- Surfaces to be painted must be cleaned thoroughly and dry and free from contaminations, grease and other foreign matters.
- Avoid painting when the moisture content and alkalinity of the walls are still high.

Application

1. Apply Kapci sealer 751 in one coat;
2. Apply Kapci Putty 750 in two or three cross layers;
3. Surface sanding;
4. Apply Kapci Coat 730 in one or two coats (tinted according to desired granulite shade);
5. Apply Kapci Granulite 789 in one coat after dilution with water up to 40% to reach the application viscosity;

Drying time at 25 °C & 60% R.H

Initial drying time 2h
Final drying time 24h

Tools for application

Spray gun

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.



KAPCI
COATINGS

Cleaner for application Tools:

water

Shelf life and Storage

Two years from production date if stored in original sealed container at normal temperature. Keep away from direct sun light.

Health and Safety

1. For full Health and Safety information, refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.