



KAPCI
COATINGS

Technical Data Sheet

Issue Date January 2024

for professional use only

Kapci Crack Filler 790

Product description:

Kapci Crack Filler 790 is high quality putty based on acrylic copolymer especially developed for use both in interior and exterior. It is used to fill cracks and holes over different kind of damaged surfaces.

Product Features

- No shrinkage
- Very good bonding to plasters
- wallboards and wooden surfaces.

Physical Properties

Color:	White
Solid content	55±3 %
Density	0.42±0.03gm/cm ³
Coverage	Depending on size and kind of damage

Substrates and surface preparation

Kapci Crack Filler 790 can be used for plaster, wallboards or wood. All new or previously painted surfaces should be free from dust, grease and waxes.

Application

1. Stir well before use;
2. It is recommended to apply suitable primer, Kapci Sealer 751 or Kapci Sealer 756, prior to applying Kapci Crack Filler 790;
3. Enlarge damage (cracks, holes, etc.) by using putty knife. Clean well by removing
4. dust and loose fine and coarse particles;
5. Apply Kapci Crack Filler 790 to get even and smooth surface;
6. Allow drying for 12h and repaint;

Drying time at 25 °C & 60% R.H



Initial drying time 15 min
Final drying time 12h

Tools for application:

Putty knife

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.



KAPCI
COATINGS

Cleaner for application tools:

water

Storage

Two years from production date if stored in original sealed container at normal temperature. Keep away from direct sun light.

Health and Safety

1. For full Health and Safety information, refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.