

	Technical Data Sheet	
Issue date January 2024		For professional use only

Kapci Art Putty 797

Product description

Kapci Art Putty 797 is waterborne putty designed to give various effects such are pharaonic blocks or any other untraditional effect according to customer needs.

Product Features

- Anti-cracking; Flexible
- Washable
- Easily applied
- Weather resistance

Physical Properties

Color:	According to Kapci color chart	
Solid content	66±3%	
Density	1.60±0.03gm/cm3	
Coverage	2.5-3 m²/kg	

Substrate and surface preparation

Kapci 797 is recommended for application over bricks, plaster, concrete and asbestos cement sheets.

Remove all loose, defective paint or powdery residues or dust.

Repair cracks, uneven surfaces with a suitable fillers or surfacer.

Smoothen the putty / filler areas with sand paper. Surfaces to be painted must be cleaned thoroughly and dry and free from contaminations, grease and other foreign matters.

Avoid painting when the moisture content and alkalinity of the walls are still high.

Application

- 1. Apply Kapci Sealer 751 or Kapci Sealer 756 in one coat;
- 2. Apply Kapci Art Putty 797 according to desired decorative effect. Dilute the putty with water up to 5% to reach the application viscosity;
- 3. Apply Kapci Top Coat 730 in one coat tinted);
- 4. Pattern the surface by color solution (Kapci UC colorant diluted by water 1:10 according to desired shade);
- 5. Apply Kapci Clear 752 in one or two coats;
- 6. To get especial effect apply Kapci Aqua Sponge 788, Kapci Reflect 780 or Kapci
- 7. Pearl 785 after the surface treatments;







Initial drying time 2h Recoating time 24h Final drying time 24h

Tools for application:

Spatula or stainless-steel putty knife

Cleaner of application tools:

water

Storage

Two years from production date if stored in original sealed container at normal temperature. Keep away from direct sun light.

Health and Safety

- 1. For full Health and Safety information, refer to the Material Safety Data Sheet (MSDS).
- 2. Observe the precautionary notices displayed on the container.
- 3. Goggles and suitable protective equipment must be worn while using these products.
- 4. Good ventilation must be provided in the working environment.