



KAPCI
COATINGS

Technical Data Sheet

Issue date January 2024

for professional use only

Kapci Aqua Sponge 799

Product description:

Kapci Aqua Sponge 799 is especially designed to give variety of attractive decorative effects to surfaces in interior.

Product Features

- High hardness
- Washable
- Easily applied
- Weather resistance
-

Physical Properties:

Color:	According to Kapci color guide
Solid content	48±3%
Density	0.90±0.03gm/cm ³
Coverage	15-20 m ² /kg

Substrate and surface preparation

- Kapci 799 is recommended for application over bricks, plaster, concrete and asbestos cement sheets.
- Remove all loose, defective paint or powdery residues or dust.
- Repair cracks, uneven surfaces with a suitable fillers or surfacer.
- Smoothen the putty / filler areas with sand paper.
- Surfaces to be painted must be cleaned thoroughly and dry and free from contaminations, grease and other foreign matters.
- Avoid painting when the moisture content and alkalinity of the walls are still high.

Application

1. Apply Kapci Sealer 751 in one coat;
2. Apply Kapci Putty 750 in two or three cross layers;
3. Surface sanding;
4. Apply Kapci Coat in one coat (tinted coat);
5. Apply Kapci Super or Kapci Super Lux (tinted according to desirable final appearance) in one or two coats. Ensure smooth surface;
6. Apply Kapci Aqua Sponge 799 in one coat after dilution with water 50%-100% to reach the application viscosity;

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.



KAPCI COATINGS

Drying time at 25 °C & 60% R.H



Initial drying time	2h
Recoating time	24h
Final drying time	7 days

Tools for application:

Roller, sponge or any application tool to get suitable finish

Cleaner for application tools:

water

Shelf Life and Storage

Two years from production date if stored in original sealed container at normal temperature. Keep away from direct sun light.

Health and Safety

1. For full Health and Safety information, refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.