

## Latico Clear 757

### Product description

Latico Clear 757 is waterborne transparent clear coat based on modified acrylic emulsion. It is recommended for both interior and exterior applications where high-quality finish is required. Latico Clear 757 is recommended for application over matt emulsion paints, masonry, bricks, plaster, concrete and cements sheets.

### Product Features

- Alkali resistant
- Washable
- Excellent non-yellowing properties
- Flexible to accommodate hair cracks in substrate

### Physical Properties

<b>Color:</b>	Transparent
<b>Viscosity</b>	8 ±3 Krebs
<b>Solid content</b>	17 ±3 %
<b>Density</b>	1 ±0.03gm/cm <sup>3</sup>
<b>Gloss</b>	High Gloss
<b>Coverage</b>	12-15 m <sup>2</sup> /kg (as ready for use product)

### Application

#### Tools for application

Roller	Brush	Spray
Recommended	Recommended to paint corners and edges.	Use airless spray or conventional spray.
		<b>Guiding data for airless spray</b> Nozzle tip                    0.015–0.021" Spray angle degrees        20°-60° Pressure at nozzle            140 - 190 kg/cm <sup>2</sup> (2100 psi)

### Surface preparation

- For new surface Apply Latico Sealer 717 in one coat; then apply Latico Putty 727, then apply again 717
  - For previously painted surfaces with alkyd paints sand, remove dust then apply Super matt 766
  - For previously painted surfaces with emulsion paints, wash surface and apply Kapci Sealer 751
1. Apply suitable type of matt emulsion paint (Latico 737 or Kapci Coat 733) in two coats;
  2. Apply Latico Clear 757 in two coats after dilution with water 100%, to reach the suitable application viscosity;

### Drying time at 25 °C & 60% R.H



Initial drying time    1h  
 Recoating time        4h  
 Final drying time     6h

### General Notes

1. Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.
2. Recommended data given is, for recoating with the same generic type of paint.
3. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.
4. The surface should be dry and free from any contamination prior to application of the subsequent coat.
5. Cleaner of application Tools is water

### Shelf Life and Storage

Two years from production date if stored in original sealed container at normal temperature. Keep away from direct sun light.

### Health and Safety

1. For full Health and Safety information, refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.