

Latico 6060 – Wood Stain

Product properties

Latico 6060 is concentrated solvent-based wood stain. It is specially designed for coloring of wooden surfaces before applying nitrocellulose, synthetic, polyester and polyurethane transparent finishes when natural look of wood is desired. It penetrates bare wood, provides fast drying and good light fastness and can be used for coloring of wooden surfaces indoor.

Theoretical coverage: 8-10 m²/l per a coat

Products for application


Latico 6060 Wood Stain

Kapci 526 NC Thinner

Substrate and surface preparation

Sand the surface of solid wood with P180 or P120 sanding paper. For plywood or veneer, use finer grit paper P220 or P180. Blow off dust and wipe off contaminants (grease, oil, etc.) prior to applying Latico 6300 NC sealer.

Application



Mixing ratio:

1 part of Latico 6060 wood stain

9 Parts of Kapci 526 NC Thinner.



Apply several coats by brush or by lint-free cotton to get the desired shade.



Dry to overcoat: 15-30 min/25°C

Other tips

1. Practical coverage depends on several factors including shape, roughness and porosity of the object to be painted, spraying equipment used, application methods, application conditions, film thickness, etc.
2. For best results, it is always recommended to test the products on scrap pieces of wood before start paint job.

Shelf life

1 year from production date stored in original packaging at normal conditions.

Health and Safety

1. For full Health and Safety information please refer to the Material Safety Data Sheet.
2. Observe the precautionary notices displayed on the container.
3. Good ventilation must be provided in the working environment.