

Latico 727 Emulsion Putty

Description

Latico 727 is waterborne putty based on vinyl-acrylic copolymer. It is used to eliminate surface imperfections over new and old cement or plaster surfaces in interior.

Products Features

- Easy to apply.
- Excellent filling ability.
- Excellent flow and leveling.
- Easy to sand.

Physical properties

Color	white
Solid content	70±3 %
Density	1.72 ±0.03gm/cm ³
Coverage	2-2.5 m ² /kg

Substrates and surface preparation

Latico 727 Emulsion putty is used for new and old cement or plaster surfaces in interior. All new or previously painted substrates should be free from dust, grease and waxes.

Application

New cement and plaster surfaces

1. Apply Kapci Sealer 751 in one coat;
2. Apply Latico 727 Emulsion putty in two cross layers;

Drying time at 25°C & 60% R.H



Initial drying time	2-3 h
Final drying time	24 h
Recoating time	24 h

Tools: Putty knife

Cleaner: water

Color: White

Shelf life

Two years from production date if stored in original sealed container at normal temperature. Keep away from direct sun light.

Health and Safety

1. For full Health and Safety information, refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.