



KAPCI
COATINGS

Technical Data Sheet

Issue: January 2026

for professional use only

Kapci K16 Paste Fast Cut Compound

Product description

Kapci K16 is a paste fast cut compound used for the removal of P1200 or finer sanding scratches. It is a silicone and wax free product which delivers a high gloss finish. Kapci K16 is used with white sponge or a wool pad. It can also be used for polish by hand.

For a superior gloss finish, apply Kapci K40 Medium Cut Compound as a second step over K16 by using yellow sponge.

Key benefits of Kapci K16

- ✓ **Speed** Fast removal of scratches
- ✓ **Finish** High gloss finishes
- ✓ **Easy to use** Simple dry use with no water addition and easy removal of the product spatter from adjacent panels
- ✓ **Permanent results** No reappearance of sanding marks

Product Placement in Kapci Polishing System

Fast Cut	Medium Cut	Fine cut	Protection
Kapci K10	Kapci K40	Kapci K60	Kapci K90
Kapci K20			Kapci 80
Kapci K15			Latico 5050
Kapci K16			
Latico 5000			

Physical, Chemical and General information

Product group	Silicone and wax free
Viscosity	N/A
Density	1.1-1.15kg/L
Shape	Paste form
Color	White
Package	1kg

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application



KAPCI
COATINGS

Technical Information and direction of use

Technical Information	
Cut	8
Gloss	6

Direction of use		
Maximum abrasion	P1200 or finer	
Polishing tool	Heavy cut foam or wool pad	
Rotational Speed	1200-1800 r.p.m	
Polishing machine	A rotary or an orbital polishing machine	Apply a small quantity of the product to the pad. Start the machine at medium speed and gradually increase the speed using light pressure.

General notes

- ✓ Apply Kapci K16 out of the direct sunlight.
- ✓ Apply Kapci K16 onto the cool surface.
- ✓ Apply Kapci K16 onto Clean surface.
- ✓ If surface is dry, a little water onto the surface can prevent dust formation.
- ✓ Reduce pressure 2-3 second before the end of rubbing process to get high gloss
- ✓ Remove residue using premium micro fiber cloth.

Storage

	Keep away from frost. Store between 15°C and 35°C. Store in well ventilated area.
---	---

Health and Safety

1. For full Health and Safety information refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and gloves should be worn while using these products.
4. Good ventilation must be provided in the working environment.

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application