



Technical Data Sheet

Issue date January 2025

for professional use only

Refinix 2K Thinners

Product description

Refinix 2K Thinners are especially designed to suite the application viscosity and the drying time of Refinix products when used in conjunction with Refinix Hardeners. Refinix Thinners optimize painting conditions and assist in delivering a reliable application process and desired finish.

Products

Product	Description	
Refinix RC45	Normal Thinner	Universal thinner for Refinix products. It adjusts the application viscosity at temperatures 15-25°C.
Refinix RC 46	Slow Thinner	Universal thinner for Refinix products. It adjusts the application viscosity at temperatures above 30°C.

Choice of thinners

Thinner	Refinix RC45 Normal thinner	Refinix RC46 Slow Thinner
Complete car or large objects	Suitable	Suitable
Partial repair	Suitable	Suitable
15°C - 25°C	Suitable	Not particularly suitable
25°C - 30°C	Suitable	Suitable
Above 30°C	Not particularly suitable	Suitable

Health and Safety

1. For full Health and Safety information please refer to Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.

IMPORTANT NOTE: These TDS are for information purposes only without any obligation as we do not have control over the quality and conditions of the surface or application.